



CONSTRUCTIVE & DIMENSIONAL:



Application field:	Landscaped areas, Pathways
Construction material:	Die-cast aluminum EN AB 44100 highly resistant to oxidation
External screws:	Stainless steel A4-70 treated with highly antioxidant waterrepellent lubricating solution
Diameter:	500mm(19,68")
Height :	450mm(17,71")

ELECTRICAL FOR MODEL:

GH1050.CGXP300EN
1050.CGX.P

Description:	1 x 26 W LED 3000 K CRI>90 2967 lm
Operating Power:	110-277 V / 50-60 Hz
Number of heads:	1
Driver positioning:	Integral
Control gear type:	Electronic
Emergency kit:	0.5m Not available

ELECTRICAL FOR MODEL:

GH1050.CGXP400EN
1050.CHX.P

Description:	1 x 26 W LED 4000 K CRI>90 3012 lm
Operating Power:	110-277 V / 50-60 Hz
Number of heads:	1
Driver positioning:	Integral
Control gear type:	Electronic
Emergency kit:	0.5m Not available


OPTICAL:


Beam type	Floor grazing 4 [21°-40°] medium for model GH1050.CGXP300EN 1050.CGX.P Floor grazing 4 [41°-60°] wide for model GH1050.CGXP400EN 1050.CHX.P
Light distribution:	Symmetric
Beam directionability:	Fixed
Diffuser material:	Vandal proof polycarbonate UV resistant
Diffuser finish:	Micro-prism

LIGHTING SOURCE:

Light source:	LED
Power:	26 W
LED voltage range:	31.2-36.8V
Courrent:	700 mA
ZVEI - Led Type:	COB
Color temperature:	3000K for model GH1050.CGXP300EN 1050.CGX.P 4000K for model GH1050.CGXP400EN 1050.CHX.P
Binning:	Step MacAdam 3
Color rendering index:	CRI>90
Nominal LED emission:	2967 lm for model GH1050.CGXP300EN 1050.CGX.P 3012 lm for model GH1050.CGXP400EN 1050.CHX.P
Light source:	Included
Ambient temperature operating range:	-20 °C ÷ +35 °C

FINISH CODE:


 .05 Dark grey (matt)

 .19 Light Grey

ACCESSORIES:



Iron anchorage
base to be
cemented Kos
AC110



IP 68 connector
for through wiring
AC279



IP 68 fast
connector Small
AC204

