

CONSTRUCTIVE & DIMENSIONAL:



Application field:	Landscaped areas, Pathways
Construction material:	Die-cast aluminum EN AB 44100 highly resistant to oxidation
External screws:	Stainless steel A4-70 treated with highly antioxidant waterrepellent lubricating solution
Length:	140mm(5,51")
Width:	40mm(1,57")
Height :	300mm(11,81")

ELECTRICAL FOR MODEL:

**GH1149.BGXP300EN
1149.ETX.P**

Description:	1 x 2.9 W LED 3000 K CRI>90 367 lm
Operating Power:	110-277 V / 50-60 Hz
Number of heads:	1
Number of Circuits:	1
Driver positioning:	Integral
Control gear type:	Electronic
Cable entry:	Silicone bushing Ø 10/14 mm. Cord length 0.5m
Emergency kit:	Not available

ELECTRICAL FOR MODEL:

**GH1149.BGXP400EN
1149.EVX.P**

Description:	1 x 2.9 W LED 4000 K CRI>90 389 lm
Operating Power:	110-277 V / 50-60 Hz
Number of heads:	1
Number of Circuits:	1
Driver positioning:	Integral
Control gear type:	Electronic
Cable entry:	Silicone bushing Ø 10/14 mm. Cord length 0.5m
Emergency kit:	Not available


OPTICAL:


Light distribution:	Asymmetric
Beam directionability:	Fixed
Diffuser material:	Soda-lime tempered glass 4mm
Diffuser finish:	Micro-prism
Diffuser temperature [°C]:	< 30 °C / 86 °F

LIGHTING SOURCE:

Light source:	LED
Power:	2.9 W
LED voltage range:	6V
Courrent:	500 mA
ZVEI - Led Type:	LED
Color temperature:	3000K for model GH1149.BGXP300EN 1149.ETX.P 4000K for model GH1149.BGXP400EN 1149.EVX.P
Binning:	Step MacAdam 3
Color rendering index:	CRI>90
Nominal LED emission:	367 lm for model GH1149.BGXP300EN 1149.ETX.P 389 lm for model GH1149.BGXP400EN 1149.EVX.P
Light source:	Included
Ambient temperature operating range:	-20 °C ÷ +35 °C

FINISH CODE:

 .05 Dark grey (matt)

 .19 Light Grey

ACCESSORIES:

