



CONSTRUCTIVE & DIMENSIONAL:

Application field:	Landscaped areas, Pathways, Driveways
Construction material:	Extruded aluminum EN AW-6060 T5 / die-casting alluminum EN-AB 44100
External screws:	Stainless steel A4-70 treated with highly antioxidant waterrepellent lubricating solution
Length:	124mm(4,88")
Width:	41mm(1,61")
Height :	500mm(19,68")

ELECTRICAL FOR MODEL: GH1422.AHXO300EN 1422.AHX.O

Description:	1 x 7 W LED 3000 K CRI>85 600 lm
Operating Power:	110-277 V / 50-60 Hz
Number of heads:	1
Driver positioning:	Integral
Control gear type:	Electronic
Cable entry:	Fixture supplied with pre-wired cable H05RN-Fmm
Emergency kit:	Not available

ELECTRICAL FOR MODEL: GH1422.AHXO400EN 1422.ALX.O

Description:	1 x 7 W LED 4000 K CRI>85 650 lm
Operating Power:	110-277 V / 50-60 Hz
Number of heads:	1
Driver positioning:	Integral
Control gear type:	Electronic
Cable entry:	Fixture supplied with pre-wired cable H05RN-F
Emergency kit:	Not available

OPTICAL:

Beam type:	Bollard 1 light
Light distribution:	Symmetric
Beam directionability:	Fixed
Diffuser material:	Polycarbonate
Diffuser finish:	Opal

LIGHTING SOURCE:

Light source:	LED
Power:	7 W
ZVEI - Led Type:	LED
Color temperature:	3000K for model GH1422.AHXO300EN 1422.AHX.O 4000K for model GH1422.AHXO400EN 1422.ALX.O
Color rendering index:	CRI>90
Nominal LED emission:	600 lm for model GH1422.AHXO300EN 1422.AHX.O 650 lm for model GH1422.AHXO400EN 1422.ALX.O
Light source:	Included
Ambient temperature operating range:	-20 °C ÷ +35 °C

FINISH CODE:

.05 Dark grey (matt)	.19 Light Grey
----------------------	----------------

ACCESSORIES:



IP 68 connector
for through wiring
AC279



IP 68 fast
connector Small
AC204



plated steel
anchorage
Quadro / Tondo /
Rettangolo
AC251