

## CONSTRUCTIVE & DIMENSIONAL:

Application field:	Landscaped areas, Pathways, Driveways
Construction material:	Extruded aluminum EN AW-6060 T5 / die-casting alluminum EN-AB 44100
External screws:	Stainless steel A4-70 treated with highly antioxidant waterrepellent lubricating solution
Length:	124mm(4,88")
Width:	41mm(1,61")
Height :	800mm(31,49")

## ELECTRICAL FOR MODEL:

**GH1423.CAXO300EN**  
1423.CAX.O

Description:	1 x 11.2 W LED 3000 K CRI>85 960 lm
Operating Power:	110-277 V / 50-60 Hz
Number of heads:	1
Driver positioning:	Integral
Control gear type:	Electronic
Cable entry:	Fixture supplied with pre-wired cable H05RN-Fmm
Emergency kit:	Not available

## ELECTRICAL FOR MODEL:

**GH1423.CAXO400EN**  
1423.CBX.O

Description:	1 x 11.2 W LED 4000 K CRI>85 1040 lm
Operating Power:	110-277 V / 50-60 Hz
Number of heads:	1
Driver positioning:	Integral
Control gear type:	Electronic
Cable entry:	Fixture supplied with pre-wired cable H05RN-F
Emergency kit:	Not available


## OPTICAL:

Beam type:	Bollard 1 light
Light distribution:	Symmetric
Beam directionability:	Fixed
Diffuser material:	Polycarbonate
Diffuser finish:	Opal

## LIGHTING SOURCE:

Light source:	LED
Power:	11,2 W
ZVEI - Led Type:	LED
Color temperature:	3000K for model GH1423.CAXO300EN 1423.CAX.O 4000K for model GH1423.CAXO400EN 1423.CBX.O
Color rendering index:	CRI>90
Nominal LED emission:	960 lm for model GH1423.CAXO300EN 1423.CAX.O 1040 lm for model GH1423.CAXO400EN 1423.CBX.O
Light source:	Included
Ambient temperature operating range:	-20 °C ÷ +35 °C

## FINISH CODE:

 .05 Dark grey (matt)

 .19 Light Grey

## ACCESSORIES:



IP 68 connector  
for through wiring  
AC279



IP 68 fast  
connector Small  
AC204



plated steel  
anchorage  
Quadro / Tondo /  
Rettangolo  
AC251

