

## CONSTRUCTIVE & DIMENSIONAL:

Application field:	Walkways, Open spaces, Driveways in residential and public areas
Construction material:	Die-cast aluminum EN AB 44100 highly resistant to oxidation steel
External screws:	Stainless steel A4-70 treated with highly antioxidant water-repellent lubricating solution
Length:	185mm(7,28")
Width:	185mm(7,28")
Height :	800mm(31,49")

## ELECTRICAL FOR MODEL:

**GH1353.CGXT300EN  
1353.CHX.TP**

Description:	1 x 26 W LED 3000 K CRI>90 2967 lm
Operating Power:	110-277 V / 50-60 Hz
Number of heads:	1
Driver positioning:	Integral
Control gear type:	Electronic
Cable entry:	EPDM bushing free of halogens Ø 8/12 mm
Second cable entry:	Available
Emergency kit:	Not available

## ELECTRICAL FOR MODEL:

**GH1353.CGXT400EN  
1353.CGX.T**

Description:	1 x 26 W LED 4000 K CRI>90 3012 lm
Operating Power:	110-277 V / 50-60 Hz
Number of heads:	1
Driver positioning:	Integral
Control gear type:	Electronic
Cable entry:	EPDM bushing free of halogens Ø 8/12 mm
Second cable entry:	Available
Emergency kit:	Not available


## OPTICAL:


Beam type	Bollard 1 light
Beam angle [°]	66°
Light distribution	Symmetric
Beam directionability	Fixed
Diffuser material	Soda-lime tempered glass 3mm
Diffuser finish	Opal

## LIGHTING SOURCE:


Light source:	LED
Power:	26 W
LED voltage range:	31.2-36.8V
Courrent:	700 mA
ZVEI - Led Type:	COB
Color temperature:	3000K for model GH1353.CGXT300EN 1353.CGX.T 4000K for model GH1353.CGXT400EN 1353.CHX.T
Binning:	Step MacAdam 3
Color rendering index:	CRI>90
Nominal LED emission:	2967 lm for model GH1353.CGXT300EN 1353.CGX.T 3012 lm for model GH1353.CGXT400EN 1353.CHX.T
Light source:	Included
Ambient temperature operating range:	-20 °C ÷ +35 °C

## FINISH CODE:


 .05 Dark grey (matt)

 .19 Light Grey

## ACCESSORIES:



Iron anchorage  
base to be  
cemented Bivio  
AC123



IP 68 connector  
for through wiring  
AC279



IP 68 fast  
connector Small  
AC204

## CONSTRUCTIVE & DIMENSIONAL:

Application field:	Walkways, Open spaces, Driveways in residential and public areas
Construction material:	Die-cast aluminum EN AB 44100 highly resistant to oxidation steel
External screws:	Stainless steel A4-70 treated with highly antioxidant water-repellent lubricating solution
Length:	185mm(7,28")
Width:	185mm(7,28")
Height :	800mm(31,49")

## ELECTRICAL FOR MODEL:

**GH1356.CGXT300EN  
1356.CGX.T**

Description:	1 x 26 W LED 3000 K CRI>90 2967 lm
Operating Power:	110-277 V / 50-60 Hz
Number of heads:	1
Driver positioning:	Integral
Control gear type:	Electronic
Cable entry:	EPDM bushing free of halogens Ø 8/12 mm
Second cable entry:	Available
Emergency kit:	Not available

## ELECTRICAL FOR MODEL:

**GH1356.CGXT400EN  
1356.CHX.T**

Description:	1 x 26 W LED 4000 K CRI>90 3012 lm
Operating Power:	110-277 V / 50-60 Hz
Number of heads:	1
Driver positioning:	Integral
Control gear type:	Electronic
Cable entry:	EPDM bushing free of halogens Ø 8/12 mm
Second cable entry:	Available
Emergency kit:	Not available


## OPTICAL:


Beam type	Bollard 4 light
Beam angle [°]	66°
Light distribution	Symmetric
Beam directionability	Fixed
Diffuser material	Soda-lime tempered glass 3mm
Diffuser finish	Opal

## LIGHTING SOURCE:


Light source:	LED
Power:	26 W
LED voltage range:	31.2-36.8V
Courrent:	700 mA
ZVEI - Led Type:	COB
Color temperature:	3000K for model GH1356.CGXT300EN 1356.CGX.T 4000K for model GH1356.CGXT400EN 1356.CHX.T
Binning:	Step MacAdam 3
Color rendering index:	CRI>90
Nominal LED emission:	2967 lm for model GH1356.CGXT300EN 1356.CGX.T 3012 lm for model GH1356.CGXT400EN 1356.CHX.T
Light source:	Included
Ambient temperature operating range:	-20 °C ÷ +35 °C

## FINISH CODE:

 .05 Dark grey (matt)

 .19 Light Grey

## ACCESSORIES:



Iron anchorage  
base to be  
cemented Bivio  
AC123



IP 68 connector  
for through wiring  
AC279



IP 68 fast  
connector Small  
AC204

