



## CONSTRUCTIVE & DIMENSIONAL:

Application field:	Landscaped areas, Pathways, Driveways
Construction material:	Extruded aluminum EN AW-6060 T5 / die-casting aluminum EN-AB 44100
External screws:	Stainless steel A4-70 treated with highly antioxidant waterrepellent lubricating solution
Length:	124mm(4,88")
Width:	41mm(1,61")
Height :	2500mm(98,42")

## ELECTRICAL FOR MODEL: GH1424.ELXO300EN 1424.FNX.O

Description:	1 x 32.4 W LED 3000 K CRI>90 3024 lm
Operating Power:	110-277 V / 50-60 Hz
Number of heads:	1
Driver positioning:	Integral
Control gear type:	Electronic
Cable entry:	Fixture supplied with pre-wired cable H05RN-Fmm
Emergency kit:	Not available

## ELECTRICAL FOR MODEL: GH1424.ELXO400EN 1424.FPX.O

Description:	1 x 27.6 W LED 4000 K CRI>90 3000 lm
Operating Power:	110-277 V / 50-60 Hz
Number of heads:	1
Driver positioning:	Integral
Control gear type:	Electronic
Cable entry:	Fixture supplied with pre-wired cable H05RN-F
Emergency kit:	Not available

## OPTICAL:

Beam type:	Bollard 1 light
Light distribution:	Symmetric
Beam directionability:	Fixed
Diffuser material:	Polycarbonate
Diffuser finish:	Opal

## LIGHTING SOURCE:

Light source:	LED
Power:	32,4 W for model: GH1424.ELXO300EN 1424.FNX.O 27,6 W for model: GH1424.ELXO400EN 1424.FPX.O
LED Voltage range:	24V CV
ZVEI - Led Type:	STRIP
Binning:	Step MacAdam 3
Color rendering index:	CRI>90
Color temperature:	3000K for model GH1424.ELXO300EN 1424.FNX.O 4000K for model GH1424.ELXO400EN 1424.FPX.O
Nominal LED emission:	3024 lm for model GH1424.ELXO300EN 1424.FNX.O 3000 lm for model GH1424.ELXO400EN 1424.FPX.O
Light source:	Included
Ambient temperature operating range:	-20 °C ÷ +35 °C

## FINISH CODE:

 .05 Dark grey (matt)	 .19 Light Grey
--	--

## ACCESSORIES:

