

## CONSTRUCTIVE & DIMENSIONAL:

Application field:	Gardens, Parks, Pathways
Construction material:	Die-cast aluminum EN AB 44100 highly resistant to oxidation
External screws:	Stainless steel A4-70 treated with highly antioxidant water-repellent lubricating solution
Diameter:	228mm(8,97")
Height :	500mm(19,68")

## ELECTRICAL FOR MODEL:

**GH8203.CGFT300EN**  
8203.CGF.T

Description:	1 x 26 W LED 3000 K CRI>90 2967 lm
Operating Power:	110-277 V / 50-60 Hz
Number of heads:	1
Driver positioning:	Integral
Control gear type:	Electronic
Cable entry:	Silicone bushing Ø 10/14 mm
Emergency kit:	Not available

## ELECTRICAL FOR MODEL:

**GH8203.CGFT400EN**  
8203.CHF.T

Description:	1 x 26 W LED 4000 K CRI>90 3012 lm
Operating Power:	110-277 V / 50-60 Hz
Number of heads:	1
Driver positioning:	Integral
Control gear type:	Electronic
Cable entry:	Silicone bushing Ø 10/14 mm
Emergency kit:	Not available

## OPTICAL:

Beam type:	Bollard [360° emission]
Beam angle:	360°
Light distribution:	Symmetric
Beam directionability:	Fixed
Diffuser material:	Vandal proof polycarbonate UV resistant
Diffuser finish:	Clear




## LIGHTING SOURCE:

Light source:	LED
Power:	26W
LED voltage range:	31.2-36.8V
Current:	700 mA
ZVEI - Led Type:	COB
Color temperature:	3000K for model GH8203.CGFT300EN 8203.CGF.T 4000K for model GH8203.CGFT400EN 8203.CHF.T
Binning:	Step MacAdam 3
Color rendering index:	CRI>90
Nominal LED emission:	2967 lm for model GH8203.CGFT300EN 8203.CGF.T 3012 lm for model GH8203.CGFT400EN 8203.CHF.T
Light source:	Included
Ambient temperature operating range:	-20 °C ÷ +35 °C

## FINISH CODE:

 .05 Dark grey (matt)	 .19 Light Grey
--	--

## ACCESSORIES:

		
Iron anchorage base to be cemented h.200 mm Tret AC121	IP 68 connector for through wiring AC279	IP 68 fast connector Small AC204