



CODE:

GH1981.FAXT300EN

GENERAL INFORMATION:

Application field: Porch, balconies & terraces, Pathios, Covered entrances & walkways, Tables

CONSTRUCTIVE & DIMENSIONAL:

Construction material: Aluminum
 External screws: Stainless steel A4-70 treated with highly antioxidant water repellent lubricating solution
 Diameter: 325mm(12,79")
 Height: 1400mm(55,11")

ELECTRICAL:

Description: 1 x 12 W LED 3000 K CRI>85 1300 lm
 Operating Power: 110-277V/50-60HZ
 Number of heads: 1
 Number of circuits: 1
 Driver positioning: Integral
 Control gear type: Electronic
 Cord Length: 5m
 Emergency kit: not available

OPTICAL:

Beam type: Table-Floor Lamp
 Light distribution: Light distribution diffused
 Beam directionability: Fixed
 Diffuser material: Polycarbonate
 Diffuser finish: Clear
 Diffuser temperature [°C]: < 40°C / 104°F

LIGHT SOURCE:

Light source: LED
 Power: 12W
 ZVEI - LED Type: DOB
 Color temperature: 3000K
 Color rendering index: CRI>85
 Nominal LED emission: 1300 lm
 Light source: Included
 Ambient temperature operating range: -20 °C ÷ +35 °C

FINISH CODES:

 .01 White (matt)	 .02 Black (matt)	 .05 Dark grey (matt)
 .19 Light Grey	 .25 White & Gold	 .26 Luxury Bronze
 .62 Antique Grey	 .71 White & Red	 .80 Sand