



MINITONDO 300 PLUG & PLAY 360°

GH1905.AHXT300EN05	Anthracite grey
GH1905.AHXT300EN19	Light grey

GENERAL INFORMATION:

Application field	Interior & exterior environments, Gardens, Area lighting, Private residences
-------------------	--

CONSTRUCTIVE & DIMENSIONAL:

Construction material	Extruded aluminum EN AW-6060 T5 high resistance to oxidation
External screws	Stainless steel A4-70 treated with highly antioxidant waterrepellent lubricating solution
Diameter	60mm(2,36")
Height	300mm(11,81")

ELECTRICAL:

Description	1 x 6 W LED 3000 K CRI>90 788 lm
Operating Power [V/mA]	110-277V/50-60HZ
Number of heads	1
Number of circuits	1
Driver positioning	Integral
Control gear type	Electronic
Cord Length	5
Emergency kit	not available

OPTICAL:

Beam type	Emission 360°
Light distribution	Symmetric
Beam directionability	Fixed
Diffuser material	Metacrilate, Polycarbonate
Diffuser temperature [°C]	< 30 °C / 86 °F
Reflector materia	Thermopolymer with high vacuum deposited aluminium

LIGHT SOURCE:

Light source	LED
Power	6W
LED voltage range	31.2-36.8V
Current	180 mA
ZVEI - LED Type	LED
Color temperature	3000K
Binning	Step MacAdam 3
Color rendering index	CRI>90
Nominal LED emission	788 lm
Life Time LED	100.000h - L80 - B10
Light source	Included
Ambient temperature operating range	-20 °C ÷ +35 °C