

MINIZAC! 300 PLUG & PLAY

GH1903.AHXA300EN19	Anthracite grey
GH1903.AHXA300EN05	Light grey

CONSTRUCTIVE & DIMENSIONAL:

Construction material	Extruded aluminum EN AW-6060 T5 / die-casting aluminum ENAB 44100
External screws	Stainless steel A4-70 treated with highly antioxidant waterrepellent lubricating solution
Diameter	50mm(1,96)
Height	300mm(11,81")

ELECTRICAL:

Description	1 x 6 W LED 3000 K CRI>90 845 lm
Operating Power [V/mA]	110-277V/50-60HZ
Number of heads	1
Number of circuits	1
Driver positioning	Integral
Control gear type	Electronic
Cord Length	5
Emergency kit	not available

OPTICAL:

Beam type	Emission 180°
Light distribution	Asymmetric
Beam directionability	Fixed
Diffuser finish	Opal
Diffuser temperature [°C]	< 30 °C / 86 °F

LIGHT SOURCE:

Light source	LED
Power	6W
LED voltage range	18V
Current	350 mA
ZVEI - LED Type	COB
Color temperature	3000K
Binning	Step MacAdam 3
Color rendering index	CRI>90
Nominal LED emission	845 lm
Light source	Included
Ambient temperature operating range	-20 °C ÷ +35 °C

ACCESSORIES

Stake AC711

