
**GENERAL INFORMATION:**

Place installation: outdoor  
 Standard colour: AL - aluminium grey (similar to RAL 7040)  
 Variant colour: GR - graphite satin finish (similar to RAL 7022)  
 Environments: urban landscape, hallway, residential lighting  
 Note: 5000K on request. DALI version on request.

**PHYSICAL:**

Installation type: low pole/bollard  
 Mounting type: ground surface  
 Mounting note: supplied complete with a kit of bolts for ground anchoring.  
 Painting: Polyester powder coating, with a pluri-processed against corrosion (passed the exposure of over 1500 hours in a saline mist environment).  
 Screws: AISI 304 stainless steel screws.  
 Seals: EPDM and Silicone Rubber Gaskets.  
 Body: Corrosion resistant extruded aluminium post. Corrosion resistant die-cast aluminium body. Corrosion resistant aluminium ground fixing base.

**DIMENSIONS:**

H: Total height device 900mm(35,43")  
 D: Total diameter device 100mm(3,93")

**OPTICAL SYSTEMS:**

Opening beam: diffused  
 Optical System: Unbreakable anti UV polycarbonate diffusers

**ELECTRICAL:**

Mounting ballast type: Integral  
 Line input: Internal looping facility 3x4mm<sup>2</sup> terminal, use only (EN 60598-1) cable type H07RN-F with diameter between 7,5 and 12mm.  
 Voltage: 110-277V  
 Frequency: 50-60Hz


**MODELS:**

Source Type:	Power:	Flux:	K:	Control:	Code:
LED COB	10W	493 lm	4000K CRI>80	ON-OFF.	D53/T190-84-AL
LED COB	10W	466 lm	3000K CRI>90	ON-OFF.	D53/T190-83-AL
LED COB	10W	493 lm	4000K CRI>80	DALI.	D53/T190-84-DD-AL
LED COB	10W	466 lm	3000K CRI>90	DALI.	D53/T190-83-DD-AL

**MOUNTING:**



Accessory code:	D53/1-TF
Technical description:	For models: D53 polo/T1, D58 box/B0/B1 and PLANO bollard. Counter plate with stay bolts.
Built-in depth:	140mm



**OPTICAL:**



Accessory code:	D53/T1-SO
Technical description:	Darkening sector -180° wide.