

CONSTRUCTIVE & DIMENSIONAL:

Application field:	Porch, balconies, terraces, passageways, pathios, covered entrances, walkways
Construction material:	Anticorodal aluminum 6082, Extruded aluminum EN AW-6060 T5 high resistance to oxidation
External screws:	Stainless steel A4-70 treated with highly antioxidant water-repellent lubricating solution
Diameter:	325mm(12,79")

ELECTRICAL FOR MODEL: GH1999.FAXT300EN

Description:	1 x 12 W LED 3000 K CRI>85 1300 lm
Operating Power:	110-277V / 50-60 Hz
Number of heads:	1
Number of circuits:	1
Driver positioning:	Integral
Control gear type:	Electronic
Cable entry:	Fixture supplied with pre-wired cable
Cord length:	0,5m
Emergency kit:	Not available








OPTICAL:

Beam type:	Ceiling downlight [60°-120°] extrawide
Light distribution:	Light distribution diffused
Beam directionability:	Fixed
Diffuser material:	Polycarbonate
Diffuser finish:	Clear
Diffuser temperature:	< 40 °C / 104 °F

LIGHTING SOURCE:

Light source:	LED
Power:	12W
ZVEI - Led Type:	DOB
Color temperature:	3000K
Color rendering index:	CRI>85
Nominal LED emission:	1300 lm
Light source:	Included
Ambient temperature operating range:	-20 °C ÷ +35 °C

FINISH CODE:

 .01 White (matt)	 .02 Black (matt)	 .26 Luxury Bronze
 .45 Corten	 .62 Antique Grey	 .65 Blue
 .80 Sand		

