

Hanging lamp

Versions: lighting.

Material: Polyethylene.


Dimensions: Ø 30 x 80/130 cm

Weight: 1,7/2 Kg

Packaging: 31 x 31 x 31 cm

Packaging volume: 0,03 m3

DIMENSIONS (cm)		
CODE	<p>LP SFT080 lighting IN GLOSSY/SATIN BRASS</p>	<p>LP SFT130 lighting IN GLOSSY/SATIN BRASS</p>
LIGHTING	<p>1x 15W</p> <p>Energy saving bulb recommended (not included).</p>	
COLOURS	<p>LIGHTING</p> <p>○ LIGHT WHITE (code LA)</p>	



Hanging lamp

Versions: lighting.

Material: Polyethylene.


Dimensions: Ø 40 h 90/140 cm

Weight: 2,5/2,8 Kg

Packaging: 41 x 41 x 41 cm

Packaging volume: 0,069 m3

DIMENSIONS (cm)		
CODE	<p>LP SFT090 lighting OUT GLOSSY/SATIN BRASS</p>	<p>LP SFT140 lighting OUT GLOSSY/SATIN BRASS</p>
LIGHTING	<p>1x 25W</p> <p>Energy saving bulb recommended (not included).</p>	
COLOURS	<p>LIGHTING</p> <p>○ LIGHT WHITE (code LA)</p>	



BULLARD BOLLARDS

SYMBOLS

- For indoor use.
- Stackable item.
- For indoor and outdoor use.
- 100% recyclable polyethylene.
- Outdoor version on request (IP55).
- European Community registered model.


LIGHTING SYMBOLS

- Protected against the intrusion of solid objects $\varnothing > 12$ mm, not against water.
- Protected against the intrusion of solid objects $\varnothing > 1$ mm and splashing water.
- Protected against the intrusion of dust and water jets.
- Fully protected against the intrusion of dust and immersion in water.
- Small lamp base for E14 - 14 mm light bulb.
- Medium lamp base for E26 - 26 mm light bulb.
- Lamp base for G4 halogen bulb.
- Lamp base for GU10 spotlight.
- Lamp base for G13 neon tube. Neon tube lighting system.
- LED technology lighting system.
- RGB lighting system.
- Item compatible with Candy Light.
- Insulation class 1.
- Insulation class 2.
- Insulation class 3.
- Device proper to direct assembly onto normally inflammable surfaces.
- Lighting through energy saving bulb. The upper figure shows the number of allowed bulbs. The lower figure shows the MAXIMUM recommended power.
- Lighting through energy saving fluorescent spotlight. The upper figure shows the number of allowed spotlights. The lower figure shows the MAXIMUM recommended power.
- Lighting through neon tube. The upper figure shows the number of allowed neon tubes. The lower figure shows the MAXIMUM recommended power.
- Lighting through energy saving globe bulb. The upper figure shows the number of allowed bulbs. The lower figure shows the MAXIMUM recommended power.
- Lighting through flexible LED tube. The lower figure shows the MAXIMUM recommended power.
- Lighting through circular T9 neon tube. The upper figure shows the number of allowed neon tubes. The lower figure shows the MAXIMUM recommended power.

MATERIAL PROPERTIES

Material: Linear low-density polyethylene - LLDPE.
 Production process: rotational moulding.
 Resistant to extreme temperatures (-60°C to +80°C).
 UV resistant (except for lighting colours).
 High tensile strength.






BULLARD BOLLARDS

WIRING SYMBOLS



I1
Wiring with metal clamp.
IP20 protection.
Diameter 11 cm.



**LED
3W**
Wiring with special base for KIT LED 3 WATT.
IP55 protection.
Diameter 11,6 cm.



**E1
SMALL**
Wiring with metal base.
IP55 protection.
Diameter 10 cm. Fastening by hex screw key.




**E3/I3
SMALL**
Wiring with plastic screw base.
I3 - IP20 protection. E3 - IP55 protection.
Diameter 6 cm.



**E1
LARGE**
Wiring with metal base.
IP55 protection.
Diameter 20 cm. Fastening by hex screw key.



**E3/I3
MEDIUM**
Wiring with plastic screw base.
I3 - IP20 protection. E3 - IP55 protection.
Diameter 10 cm.



I2 / E2
Wiring with plastic base and metal inserts.
I2 - IP20 protection. E2 - IP55 protection.
Diameter 10 cm. Fastening by slot screwdriver.



**E3/I3
LARGE**
Wiring with plastic screw base.
I3 - IP20 protection. E3 - IP55 protection.
Diameter 15 cm.



**CANDY
LIGHT**
Wiring with plastic base and LED CANDY LIGHT.
IP44 protection.
Diameter 10 cm.



**CUSTOM
BASE**
Special metal base.
IP20 protection.
Several sizes.