



**CODE:**

A-760

**DIMENSIONS:**

Height (KK): 46" / 48" / 56" / 62" / CUS\*

Diameter(FF): 8" / 10" / 12" (choose depending on a security rating needed\*)

**BOLLARD COVER MATERIAL(BB):**

- 01. Stainless steel
- 02. Carbon Steel
- 03. Aluminum

**FINISHES(QQ):**

- 11 316 Stainless steel with a #4 swirl brushed stainless surface finish
- 12 Custom RAL

Stainless powder coated standard colors:

- 30. Black
- 33. White
- 36. Dark Grey
- 40. Light Grey

**SECURITY RATING(RR):**

Please Read our Crash Rating guidance

BDS-C40FB36-ST	ASTM C40 CRASH RATED FIXED BOLLARD
BDS-C40RB36-ST	ASTM C40 CRASH RATED REMOVABLE BOLLARD
BDS-M30-FB-ST	ASTM M30 CRASH RATED FIXED BOLLARD
BDS-M30-RB-ST	ASTM M30 CRASH RATED REMOVABLE BOLLARD
BDS-M30FB-SH	ASTM M30 CRASHED RATED SHALLOW BOLLARD
BDS-M30RB-SH	ASTM M30 CRASHED RATED SHALLOW BOLLARD
BDS-PU40FB36-ST	ASTM PU40 CRASH RATED FIXED BOLLARD
BDS-PU40RB36-ST	ASTM PU40 CRASH RATED REMOVABLE BOLLARD
BDS-H40FB-ST	ASTM H40 CRASH RATED FIXED BOLLARD
BDS-H40RB-ST	ASTM H40 CRASH RATED REMOVABLE BOLLARD
BDS-H30FB-ST	ASTM H30 CRASH RATED FIXED BOLLARD
BDS-H30RB-ST	ASTM H30 CRASH RATED REMOVABLE BOLLARD

**COLOUR TEMPERATURE(JJ):**

- 31 3000K
- 32 4000K

**GENERAL CHARACTERISTICS:**

Voltage:	110-277V
Wattage:	9W
Source Type:	LED
Operating Temperature:	-22°F~122°F
IP Rating:	IP 65
CRI	90
FLUX:	720lm
Dimmable	0-10V

