







CONSTRUCTIVE & DIMENSIONAL:

| | |
|------------------------|---|
| Application field: | Porch, balconies & terraces, General lighting, Covered entrances & walkways |
| Gaskets: | Silicone gaskets |
| Construction material: | Extruded aluminum EN AW-6060 T5 high resistance to oxidation |
| External screws: | Stainless Steel A4 |
| Length: | 117mm(4.61") |
| Width: | 117mm(4.61") |
| Cutout shape: | Square |
| Recessed depth: | 92mm(3.62") |



ELECTRICAL:

GH2002.BRYT300EN

| | |
|---|---|
| Description: | 1 x 13.5 W LED 3000 K CRI>90 1 x 1312 lm |
| Luminaire efficiency: [lm/W] | 62.34 |
| Fixture consumption: | 15.88 W |
| Operation Range: | 110-277V - 50/60 Hz |
| Number of circuits: | 1 |
| Driver positioning: | Integral |
| Control gear type: | Electronic |
| Cable entry: | Nylon cable gland M12 Ø 3,5/7 mm |
| Daisy chain wiring: | External to the luminaire with IP68 connector available as an accessory |
| Cable type: | FR5FOEM7-AD8 2x0.5mm2 |
| Cord length: [m] | 0.5 |
| Emergency: | Available upon request - not integrated into the luminaire |
| Ambient temperature operating range: [°C] | -20 °C ÷ +35 °C |

OPTICAL:

| | |
|----------------------------|---------------------------------------|
| Beam angle: [°] | 19° x 32° |
| Light distribution: | 2 Axis symmetrical |
| Beam directionability: | Fixed optics |
| Glare index: | UGR < 16 |
| Diffuser material: | Tempered glass 5mm |
| Diffuser finish: | Transparent - extra clear |
| Diffuser temperature: [°C] | < 50 °C |
| Optics: | Anti UV technopolymer lens |
| Secondary optics: | Black anti UV technopolymer reflector |

LIGHTING SOURCE,

| | |
|-----------------------------|---------------------|
| Light source: | LED |
| Light source: [W] | 13.5 W |
| Nominal LED emission: [Lm] | 1312 lm |
| Color temperature: | 3000 K |
| Binning: | Step MacAdam 3 |
| LED voltage range: [V] | 27 V |
| Current: | 500 mA |
| Luminaire emission [lm] | 1 x 990 |
| LED / Bulb: | Included |
| Color rendering index: Life | CRI>90 |
| Time LED [t]: | 60.000h - L80 - B10 |

| H(m) | φ(m) | lux med. 3000 K | lux max. 3000 K |
|------|------|--------------------|--------------------|
| 5 | 1.7 | 103 | 164 |
| 4 | 1.4 | 161 | 256 |
| 3 | 1.0 | 287 | 455 |
| 2 | 0.7 | 645 | 1023 |
| 1 | 0.3 | 2579 | 4092 |



sales@gordonbullard.com
www.bullardbollards.com
1-877-964-4646



991 South Gull Lake
Dr Richland, MI
49083 USA



FINISH OPTIONS:

Standard Colors

● .05 Anthracite grey (matt)

● .19 Light grey (matt)

Up-On Request Colors

● .01 White (matt)

● .02 Black (matt)

● .45 Corten (matt)

● .26 Luxury bronze




● .62 Antique grey (matt)

● .65 Blue (matt)

● .80 Sand (matt)

● .83 Green (matt)

ACCESSORIES:



Accessory for installation
Edge R SQ Frame
AC457



Accessory for installation
Edge R SQ Trimless
AC459

| H(m) | φ(m) | lux med. 3000 K | lux max. 3000 K |
|------|------|--------------------|--------------------|
| 5 | 1.7 | 103 | 164 |
| 4 | 1.4 | 161 | 256 |
| 3 | 1.0 | 287 | 455 |
| 2 | 0.7 | 645 | 1023 |
| 1 | 0.3 | 2579 | 4092 |



sales@gordonbullard.com
www.bullardbollards.com
1-877-964-4646







991 South Gull Lake
Dr Richland, MI
49083 USA



CONSTRUCTIVE & DIMENSIONAL:

| | |
|------------------------|---|
| Application field: | Porch, balconies & terraces, General lighting, Covered entrances & walkways |
| Gaskets: | Silicone gaskets |
| Construction material: | Extruded aluminum EN AW-6060 T5 high resistance to oxidation |
| External screws: | Stainless Steel A4 |
| Length: | 117mm(4.61") |
| Width: | 117mm(4.61") |
| Cutout shape: | Square |
| Recessed depth: | 92mm(3.62") |



ELECTRICAL:

GH2002.BRYT400EN

| | |
|---|---|
| Description: | 1 x 13.5 W LED 4000 K CRI>90 1 x 1455 lm |
| Luminaire efficiency: [lm/W] | 69.14 |
| Fixture consumption: | 15.88 W |
| Operation Range: | 110-277V - 50/60 Hz |
| Number of circuits: | 1 |
| Driver positioning: | Integral |
| Control gear type: | Electronic |
| Cable entry: | Nylon cable gland M12 Ø 3,5/7 mm |
| Daisy chain wiring: | External to the luminaire with IP68 connector available as an accessory |
| Cable type: | FR5FOEM7-AD8 2x0.5mm2 |
| Cord length: [m] | 0.5 |
| Emergency: | Available upon request - not integrated into the luminaire |
| Ambient temperature operating range: [°C] | -20 °C ÷ +35 °C |

OPTICAL:

| | |
|----------------------------|---------------------------------------|
| Beam angle: [°] | 19° x 32° |
| Light distribution: | 2 Axis symmetrical |
| Beam directionability: | Fixed optics |
| Glare index: | UGR < 16 |
| Diffuser material: | Tempered glass 5mm |
| Diffuser finish: | Transparent - extra clear |
| Diffuser temperature: [°C] | < 50 °C |
| Optics: | Anti UV technopolymer lens |
| Secondary optics: | Black anti UV technopolymer reflector |

LIGHTING SOURCE,

| | |
|-----------------------------|---------------------|
| Light source: | LED |
| Light source: [W] | 13.5 W |
| Nominal LED emission: [Lm] | 1455 lm |
| Color temperature: | 4000 K |
| Binning: | Step MacAdam 3 |
| LED voltage range: [V] | 27 V |
| Current: | 500 mA |
| Luminaire emission [lm] | 1 x 1098 |
| LED / Bulb: | Included |
| Color rendering index: Life | CRI>90 |
| Time LED [t]: | 60.000h - L80 - B10 |

| H(m) | φ (m) | lux med. 4000 K | lux max. 4000 K |
|------|-------|--------------------|--------------------|
| 5 | 1.7 | 114 | 182 |
| 4 | 1.4 | 179 | 284 |
| 3 | 1.0 | 318 | 504 |
| 2 | 0.7 | 715 | 1135 |
| 1 | 0.3 | 2860 | 4538 |



sales@gordonbullard.com
www.bullardbollards.com
1-877-964-4646



991 South Gull Lake
Dr Richland, MI
49083 USA



FINISH OPTIONS:

Standard Colors

● .05 Anthracite grey (matt)

● .19 Light grey (matt)

Up-On Request Colors

● .01 White (matt)

● .02 Black (matt)

● .45 Corten (matt)

● .26 Luxury bronze





● .62 Antique grey (matt)

● .65 Blue (matt)

● .80 Sand (matt)

● .83 Green (matt)

ACCESSORIES:



Accessory for installation
Edge R SQ Frame
AC457



Accessory for installation
Edge R SQ Trimless
AC459

| H(m) | φ (m) | lux med. 4000 K | lux max. 4000 K |
|------|-------|--------------------|--------------------|
| 5 | 1.7 | 114 | 182 |
| 4 | 1.4 | 179 | 284 |
| 3 | 1.0 | 318 | 504 |
| 2 | 0.7 | 715 | 1135 |
| 1 | 0.3 | 2860 | 4538 |



sales@gordonbullard.com
www.bullardbollards.com
1-877-964-4646



991 South Gull Lake
Dr Richland, MI
49083 USA