

H(m)	Φ(m)	Lux Medi	Lux Max
5	0	0	0
4	0	0	0
3	0	0	0
2	0	0	0
1	0	0	0

CONSTRUCTIVE & DIMENSIONAL:

Application field:	Series of spot lights to be mounted on floor, wall, spike, tree with belt system or on a pole system.
Gaskets:	Silicone gaskets
Construction material:	Stainless steel AISI 316L, Extruded aluminum EN AW-6063 T5 high resistance to oxidation
External screws:	Stainless steel A4-70 treated with highly antioxidant water-repellent lubricating solution
Diameter:	45mm(1.77")
Length:	47mm(1.85")
Height / Projection:	73cm(2.87")

ELECTRICAL: GH1115.BGFT300EL

Number of heads:	1
Description:	1 x 2.1 W LED 3000 K CRI>90 1 x 196 lm
Luminaire efficiency:	44.47 lm/W
Fixture consumption:	2.8 W
Operation Range:	24 V DC
Number of circuits:	1
Driver positioning:	Remote
Control gear:	24 V DC not included
Control gear type:	Electronic
Cable entry:	Brass cable gland M12 Ø 3.5/7 mm
Dimmer type:	Dim based on driver
Daisy chain wiring:	External to the luminaire with IP68 connector available as an accessory
Cable type:	FR5FOEM7-AD8 2x0.5mm2
Cord length:	0.5m
Emergency:	Not available
Ambient temperature operating range:	-20 °C ÷ +35 °C



OPTICAL:

Beam angle:	36°
Swivel:	+/- 90°
Light distribution:	Symmetrical medium flood (15° - 45°)
Beam directionability:	Adjustable
Diffuser material:	Tempered glass 4mm
Diffuser finish:	Transparent - extra clear
Optics:	Anti UV technopolymer lens

LIGHTING SOURCE,

Light source:	LED
Type of bulb or LED:	COB
Light source:	2.1 W
Nominal LED emission:	196 lm
Color temperature:	3000K
Binning:	Step MacAdam 3
LED voltage range:	3V
Current:	700 mA
Color rendering index:	CRI90
Life Time LED:	60.000h - L80 - B10 [t]
Luminaire emission:	1 x 125lm
LED / Bulb:	Included





FINISH OPTIONS:

Standard Finishes

● .05 Anthracite grey (matt)

● .19 Light grey (matt)

Upon Request Finishes

● .01 White (matt)

● .02 Black (matt)

● .45 Corten (matt)

● .26 Luxury bronze

● .62 Antique grey (matt)

● .65 Blue (matt)

● .80 Sand (matt)

● .83 Green (matt)

ACCESSORIES:



Stake 170mm AC203



Hood Segno - Point Spot 2 AC647



IP 68 fast connector 4P AC204

DIMMING TYPE:

- 101. Non-dimmable
- 102. 0-10V dimmable

H(m)	Φ(m)	Lux Medi	Lux Max
5	0	0	0
4	0	0	0
3	0	0	0
2	0	0	0
1	0	0	0






sales@gordonbullard.com
 www.bullardbollards.com
 1-877-964-4646



991 South Gull Lake
 Dr Richland, MI
 49083 USA



CONSTRUCTIVE & DIMENSIONAL:



H(m)	φ(m)	lux med. 4000 K	lux max. 4000 K
5	5.2	20	37
4	4.1	31	57
3	3.1	54	101
2	2.1	123	228
1	1.0	490	913



Application field: Series of spot lights to be mounted on floor, wall, spike, tree with belt system or on a pole system.

Gaskets: Silicone gaskets

Construction material: Stainless steel AISI 316L, Extruded aluminum EN AW-6063 T5 high resistance to oxidation

External screws: Stainless steel A4-70 treated with highly antioxidant water-repellent lubricating solution

Diameter: 45mm(1.77")

Length: 47mm(1.85")

Height / Projection: 73cm(2.87")

ELECTRICAL: GH1115.BGFT400EL

Number of heads: 1

Description: 1 x 2.1 W LED 4000 K CRI>90 1 x 218 lm

Luminaire efficiency: 49.46 lm/W

Fixture consumption: 2.8 W

Operation Range: 24 V DC

Number of circuits: 1

Driver positioning: Remote

Control gear: 24 V DC not included

Control gear type: Electronic

Cable entry: Brass cable gland M12 Ø 3.5/7 mm

Dimmer type: Dim based on driver

Daisy chain wiring: External to the luminaire with IP68 connector available as an accessory

Cable type: FR5FOEM7-AD8 2x0.5mm2

Cord length: 0.5m

Emergency: Not available

Ambient temperature operating range: -20 °C ÷ +35 °C

OPTICAL:

Beam angle: 36°

Swivel: +/- 90°

Light distribution: Symmetrical medium flood (15° - 45°)

Beam directionability: Adjustable

Diffuser material: Tempered glass 4mm

Diffuser finish: Transparent - extra clear

Optics: Anti UV technopolymer lens

LIGHTING SOURCE:

Light source: LED

Type of bulb or LED: COB

Light source: 2.1 W

Nominal LED emission: 218 lm

Color temperature: 4000K

Binning: Step MacAdam 3

LED voltage range: 3V

Current: 700 mA

Color rendering index: CRI90

Life Time LED: 60.000h - L80 - B10[t]




Luminaire emission: 1 x 138lm

LED / Bulb: Included

sales@gordonbullard.com
www.bullardbollards.com
1-877-964-4646



991 South Gull Lake
Dr Richland, MI
49083 USA



H(m)	φ(m)	lux med. 4000 K	lux max. 4000 K
5	5.2	20	37
4	4.1	31	57
3	3.1	54	101
2	2.1	123	228
1	1.0	490	913



FINISH OPTIONS:

Standard Finishes

●.05 Anthracite grey (matt)

●.19 Light grey (matt)

Upon Request Finishes

●.01 White (matt)

●.45 Corten (matt)

●.62 Antique grey (matt)

●.80 Sand (matt)

●.02 Black (matt)

●.26 Luxury bronze

●.65 Blue (matt)

●.83 Green (matt)

ACCESSORIES:



Stake 170mm
AC203



Hood Maxiseigno - Point
Spot 3
AC648



IP 68 fast connector 4P
AC204

DIMMING TYPE:

- 101. Non-dimmable
- 102. 0-10V dimmable

sales@gordonbullard.com
www.bullardbollards.com
1-877-964-4646



991 South Gull Lake
Dr Richland, MI
49083 USA