







CONSTRUCTIVE & DIMENSIONAL:



| H(m) | φ (m) | lux med. 3000 K | lux max. 3000 K |
|------|-------|--------------------|--------------------|
| 5 | 2.2 | 82 | 130 |
| 4 | 1.8 | 127 | 203 |
| 3 | 1.3 | 226 | 360 |
| 2 | 0.9 | 509 | 810 |
| 1 | 0.4 | 2038 | 3241 |

| | |
|------------------------|--|
| Application field: | Series of linear fixtures to be recessed in the ceiling with very low recess depth characterized by high level of visual comfort. |
| Gaskets: | Silicone gaskets |
| Construction material: | Stainless steel AISI 316L, Extruded aluminum EN AW-6060 T5 high resistance to oxidation, Die-cast aluminum EN AB 44100 highly resistant to oxidation |
| External screws: | Stainless steel A4-70 treated with highly antioxidant water-repellent lubricating solution |
| Length: | 380mm(15") |
| Width: | 75mm(2.95") |
| Height / Projection: | 3mm(0.118") |
| Cutout shape: | Rectangular |
| Cutout length: | 430mm(17") |
| Cutout width: | 71mm(2.80") |
| Recessed depth: | 90mm(3.54") |
| Rough in housing: | Polypropylene to be ordered separately |
| Drainage: | 300mm(11.8") of gravel or draining material. Alternatively, draining piping system. |
| Static load: | 500KG |

ELECTRICAL:

GH1080.LVMT300EN

| | |
|---|---|
| Description: | 1 x 9 W LED 3000 K CRI>90 1 x 876 lm |
| Luminaire efficiency: [lm/W] | 64.48 |
| Fixture consumption: | 10.59 W |
| Operation Range: | 110-277V - 50/60 Hz |
| Number of circuits: | 1 |
| Driver positioning: | Integral |
| Control gear type: | Electronic |
| Dimmer type: | DALI on request |
| Cable entry: | Nylon cable gland M20 Ø 7/13 mm |
| Daisy chain wiring: | External to the luminaire with IP68 connector available as an accessory |
| Cable type: | H07RN8-F 3x1mm ² |
| Cord length: [m] | 0.5 |
| Water-Lock system: | Included |
| Ambient temperature operating range: [°C] | -20 °C ÷ +35 °C |

OPTICAL:





| | |
|----------------------------|------------------------------------|
| Beam angle: [°] | 25° |
| Light distribution: | Symmetrical wide beam (45° - 125°) |
| Beam directionability: | Fixed optics |
| Diffuser material: | Tempered glass 8mm |
| Diffuser finish: | Transparent - extra clear |
| Diffuser temperature: [°C] | < 40 °C |
| Optics: | Anti UV technopolymer lens |



sales@gordonbullard.com
www.bullardbollards.com
1-877-964-4646



991 South Gull Lake
Dr Richland, MI
49083 USA



| H(m) | φ (m) | lux med. 3000 K | lux max. 3000 K |
|------|-------|-----------------|-----------------|
| 5 | 2.2 | 82 | 130 |
| 4 | 1.8 | 127 | 203 |
| 3 | 1.3 | 226 | 360 |
| 2 | 0.9 | 509 | 810 |
| 1 | 0.4 | 2038 | 3241 |



LIGHTING SOURCE,

| | |
|----------------------------|---------------------|
| Light source: | LED |
| Type of bulb or LED: | LED MODULE |
| Light source: [W] | 9 W |
| Nominal LED emission: [Lm] | 876 lm |
| Color temperature: | 3000 K |
| Binning: | Step MacAdam 3 |
| LED voltage range: [V] | 18V |
| Courrent: | 500 mA |
| Luminaire emission [lm] | 1 x 683 |
| LED / Bulb: | Included |
| Color rendering index: | CR>90 |
| Life Time LED [t]: | 60.000h - L80 - B10 |

FINISH OPTIONS:

- .15 Stainless steel

ACCESSORIES:



IP 68 connector for through wiring 4P AC279



IP 68 fast connector 4P AC204



IP 68 fast connector 5P AC204-5P



IP 68 connector for through wiring 5P AC279-5P



Rough-in housing AC603



Ceiling brackets AC573



DALI Optional ED-20





sales@gordonbullard.com
www.bullardbollards.com
1-877-964-4646



991 South Gull Lake
Dr Richland, MI
49083 USA



CONSTRUCTIVE & DIMENSIONAL:



| H(m) | φ (m) | lux med. 4000 K | lux max. 4000 K |
|------|-------|--------------------|--------------------|
| 5 | 2.2 | 90 | 144 |
| 4 | 1.8 | 141 | 225 |
| 3 | 1.3 | 251 | 400 |
| 2 | 0.9 | 565 | 899 |
| 1 | 0.4 | 2261 | 3596 |

| | |
|------------------------|--|
| Application field: | Series of linear fixtures to be recessed in the ceiling with very low recess depth characterized by high level of visual comfort. |
| Gaskets: | Silicone gaskets |
| Construction material: | Stainless steel AISI 316L, Extruded aluminum EN AW-6060 T5 high resistance to oxidation, Die-cast aluminum EN AB 44100 highly resistant to oxidation |
| External screws: | Stainless steel A4-70 treated with highly antioxidant water-repellent lubricating solution |
| Length: | 380mm(15") |
| Width: | 75mm(2.95") |
| Height / Projection: | 3mm(0.118") |
| Cutout shape: | Rectangular |
| Cutout length: | 430mm(17") |
| Cutout width: | 71mm(2.80") |
| Recessed depth: | 90mm(3.54") |
| Rough in housing: | Polypropylene to be ordered separately |
| Drainage: | 300mm(11.8") of gravel or draining material. Alternatively, draining piping system. |
| Static load: | 500KG |

ELECTRICAL:

GH1080.LVMT400EN

| | |
|---|---|
| Description: | 1 x 9 W LED 4000 K CRI>90 1 x 972 lm |
| Luminaire efficiency: [lm/W] | 76.09 |
| Fixture consumption: | 10.59 W |
| Operation Range: | 110-277V - 50/60 Hz |
| Number of circuits: | 1 |
| Driver positioning: | Integral |
| Control gear type: | Electronic |
| Dimmer type: | DALI on request |
| Cable entry: | Nylon cable gland M20 Ø 7/13 mm |
| Daisy chain wiring: | External to the luminaire with IP68 connector available as an accessory |
| Cable type: | H07RN8-F 3x1mm ² |
| Cord length: [m] | 0.5 |
| Water-Lock system: | Included |
| Ambient temperature operating range: [°C] | -20 °C ÷ +35 °C |

OPTICAL:





| | |
|----------------------------|-----------------------------------|
| Beam angle: [°] | 50° |
| Light distribution: | Symmetrical wide beam (15° - 45°) |
| Beam directionability: | Fixed optics |
| Diffuser material: | Tempered glass 8mm |
| Diffuser finish: | Transparent - extra clear |
| Diffuser temperature: [°C] | < 40 °C |
| Optics: | Anti UV technopolymer lens |



sales@gordonbullard.com
www.bullardbollards.com
1-877-964-4646



991 South Gull Lake
Dr Richland, MI
49083 USA



| H(m) | φ (m) | lux med. 4000 K | lux max. 4000 K |
|------|-------|--------------------|--------------------|
| 5 | 2.2 | 90 | 144 |
| 4 | 1.8 | 141 | 225 |
| 3 | 1.3 | 251 | 400 |
| 2 | 0.9 | 565 | 899 |
| 1 | 0.4 | 2261 | 3596 |



LIGHTING SOURCE,

| | |
|----------------------------|---------------------|
| Light source: | LED |
| Type of bulb or LED: | LED MODULE |
| Light source: [W] | 9 W |
| Nominal LED emission: [Lm] | 972 lm |
| Color temperature: | 4000 K |
| Binning: | Step MacAdam 3 |
| LED voltage range: [V] | 18V |
| Courrent: | 500 mA |
| Luminaire emission [lm] | 1 x 806 |
| LED / Bulb: | Included |
| Color rendering index: | CRI>90 |
| Life Time LED [t]: | 60.000h - L80 - B10 |

FINISH OPTIONS:

- .15 Stainless steel

ACCESSORIES:



IP 68 connector for through wiring 4P AC279



IP 68 fast connector 4P AC204



IP 68 fast connector 5P AC204-5P



IP 68 connector for through wiring 5P AC279-5P



Rough-in housing AC603



Ceiling brackets AC573



DALI Optional ED-20

sales@gordonbullard.com
www.bullardbollards.com
1-877-964-4646



991 South Gull Lake
Dr Richland, MI
49083 USA