

H(m)	φ (m)	lux med. 3000 K	lux max. 3000 K
5	4.3	5	9
4	3.4	8	14
3	2.6	15	25
2	1.7	33	55
1	0.9	133	222



CONSTRUCTIVE & DIMENSIONAL:

Application field:	Series of spot lights to be mounted on floor, wall, spike, tree with belt system or on a pole system.
Gaskets:	Silicone gaskets
Construction material:	Stainless steel AISI 316L, Extruded aluminum EN AW-6063 T5 high resistance to oxidation
External screws:	Stainless steel A4-70 treated with highly antioxidant water-repellent lubricating solution
Diameter:	35mm(1.37")
Length:	38mm(1.49")
Height / Projection:	58cm(2.28")
Cutout shape:	Round

ELECTRICAL:

GH114.BAFT300EC 1114.BDM.T

Number of heads:	1
Description:	1 x 2.1 W LED 3000 K CRI>90 1 x 196 lm
Luminaire efficiency:	53.8 lm/W
Fixture consumption:	2.8 W
Operation Range:	700 mA
Number of circuits:	1
Driver positioning:	Remote
Control gear:	700 mA not included
Control gear type:	Electronic
Cable entry:	Brass cable gland M12 Ø 3.5/7 mm
Dimmer type:	Dim based on driver
Daisy chain wiring:	External to the luminaire with IP68 connector available as an accessory
Cable type:	FR5FOEM7-AD8 2x0.5mm2
Cord length:	0.5m
Emergency:	Not available
Ambient temperature operating range:	-20 °C ÷ +35 °C

OPTICAL:

Beam angle:	46°
Swivel:	+/- 90°
Light distribution:	Symmetrical wide beam (45° - 125°)
Beam directionability:	Adjustable
Diffuser material:	Tempered glass 4mm
Diffuser finish:	Transparent - extra clear
Optics:	Anti UV technopolymer lens




LIGHTING SOURCE,

Light source:	LED
Type of bulb or LED	LED module
Light source:	2.1 W
Nominal LED emission:	196 lm
Color temperature:	3000K
Binning:	Step MacAdam 3
LED voltage range:	3V
Current:	700 mA
Color rendering index:	CRI90
Life Time LED:	60.000h - L80 - B10 [r]
Luminaire emission:	1 x 151lm
LED / Bulb	Included

sales@gordonbullard.com
www.bullardbollards.com
1-877-964-4646



991 South Gull Lake
Dr Richland, MI
49083 USA



H(m)	φ(m)	lux med. 3000 K	lux max. 3000 K
5	4.3	5	9
4	3.4	8	14
3	2.6	15	25
2	1.7	33	55
1	0.9	133	222



FINISH OPTIONS:

Standard Finishes

● .05 Anthracite grey (matt)

● .19 Light grey (matt)

Upon Request Finishes

● .01 White (matt)

● .45 Corten (matt)

● .62 Antique grey (matt)

● .80 Sand (matt)

● .02 Black (matt)

● .26 Luxury bronze

● .65 Blue (matt)

● .83 Green (matt)

ACCESSORIES:



Stake 170mm
AC203



Hood Segno - Point Spot 2
AC647






IP 68 fast connector 4P
AC204

DIMMING TYPE:

101. Non-dimmable

102. 0-10V dimmable



H(m)	φ (m)	lux med. 4000 K	lux max. 4000 K
5	4.3	6	10
4	3.4	9	15
3	2.6	16	27
2	1.7	37	62
1	0.9	148	247



CONSTRUCTIVE & DIMENSIONAL:

Application field:	Series of spot lights to be mounted on floor, wall, spike, tree with belt system or on a pole system.
Gaskets:	Silicone gaskets
Construction material:	Stainless steel AISI 316L, Extruded aluminum EN AW-6063 T5 high resistance to oxidation
External screws:	Stainless steel A4-70 treated with highly antioxidant water-repellent lubricating solution
Diameter:	35mm(1.37")
Length:	38mm(1.49")
Height / Projection:	58cm(2.28")
Cutout shape:	Round

ELECTRICAL:

GH1114.BAFT400EC 1114.BEM.T

Number of heads:	1
Description:	1 x 2.1 W LED 4000 K CRI>90 1 x 218 lm
Luminaire efficiency:	59.88 lm/W
Fixture consumption:	2.8 W
Operation Range:	700 mA
Number of circuits:	1
Driver positioning:	Remote
Control gear:	700 mA not included
Control gear type:	Electronic
Cable entry:	Brass cable gland M12 Ø 3.5/7 mm
Dimmer type:	Dim based on driver
Daisy chain wiring:	External to the luminaire with IP68 connector available as an accessory
Cable type:	FR5FOEM7-AD8 2x0.5mm2
Cord length:	0.5m
Emergency:	Not available
Ambient temperature operating range:	-20 °C ÷ +35 °C

OPTICAL:

Beam angle:	46°
Swivel:	+/- 90°
Light distribution:	Symmetrical wide beam (45° - 125°)
Beam directionability:	Adjustable
Diffuser material:	Tempered glass 4mm
Diffuser finish:	Transparent - extra clear
Optics:	Anti UV technopolymer lens




LIGHTING SOURCE,

Light source:	LED
Type of bulb or LED	LED module
Light source:	2.1 W
Nominal LED emission:	218 lm
Color temperature:	3000K
Binning:	Step MacAdam 3
LED voltage range:	3V
Current:	700 mA
Color rendering index:	CRI90
Life Time LED:	60.000h - L80 - B10 [r]
Luminaire emission:	1 x 168lm
LED / Bulb	Included

sales@gordonbullard.com
www.bullardbollards.com
1-877-964-4646



991 South Gull Lake
Dr Richland, MI
49083 USA



H(m)	φ(m)	lux med. 4000 K	lux max. 4000 K
5	4.3	6	10
4	3.4	9	15
3	2.6	16	27
2	1.7	37	62
1	0.9	148	247



FINISH OPTIONS:

Standard Finishes

● .05 Anthracite grey (matt)

● .19 Light grey (matt)

Upon Request Finishes

● .01 White (matt)

● .45 Corten (matt)

● .62 Antique grey (matt)

● .80 Sand (matt)

● .02 Black (matt)

● .26 Luxury bronze

● .65 Blue (matt)

● .83 Green (matt)

ACCESSORIES:



Stake 170mm
AC203



Hood Segno - Point Spot 2
AC647



IP 68 fast connector 4P
AC204

DIMMING TYPE:

101. Non-dimmable

102. 0-10V dimmable