



Esyr 6,7W

Floodlights

Code: 3234

Application

3000K

4000K

Installation with adjustable bracket or on ground with steel picket

- IP66 Floodlight with 1 led of 6.7W
- Aluminum anodized and varnished alloy body with glass front protection

~ 650

~ 680

- Installation with bracket, with steel picket or base
 Withdrawn pop-dazzling optic
- Withdrawn non-dazzling optic
- Provided with 1m of 3x1 neoprene cablePower supply unit incorporated


KELVIN	CRI	LUMEN EFFETTIVI
2700K	90	~ 510




Application				
Installation with	base	on	ceiling	

80





	_								
SHAPE	<u></u>	FINISH		<u></u>	COL	.OUR	<u></u>	OPTICALS	
Round	<u>10</u>	White		<u>3</u>		4000 K	2	20°	
		Grey	RAL 7042	<u>5</u>	0	3000 K	<u>3</u>	40°	
		Corten		<u>8</u>	0	2700 K	w	60°	
								90°	
								Diffused	



Input: 110-277V

ACCESSORIES			
307500012	Neoprene cable 3x1		
307500019	Steel picket		
307500029	Non dazzling system		



Web: www.bullardbollards.com

Tel: 1-877-964-4646



991 South Gull Lake Dr

Richland, MI 49083

USA

Due to the dynamic nature of lighting products and the associated technologies, luminaire data on all sheet sheets is subject to change at the discretion of Gordon Bullard LLC and associated companies. © copyright Gordon Bullard 2023
Updated 05/10/23