

## PRODUCT CODE:

T850

## DIMENSIONS:

Height (AA):44"/46"/48" / 50" / CUS\*

Diameter(BB): 8"/ 9"/10" /11" /12" (depending on a security rating needed\*)

## BOLLARD COVER MATERIAL(CC):

- 01 Aluminium
- 02 Stainless Steel

## LENS MATERIAL(DD):

- 10 Standard Clear Lens
- 11 Difuse acrylic lens
- 12 No lens

## FINISHES(EE):

- 21 316 Stainless steel with a #4 swirl brushed stainless surface finish
- 22 Custom RAL

Stainless powder coated standard colors:



## LIGHT DISTRIBUTION(FF):

- Type A: 180°
- Type B: 360°

## CCT(KK):

- 30 2200K
- 31 3000K
- 32 3500K
- 33 4000K

sales@gordonbullard.com  
www.bullardbollards.com  
1-877-964-4646



991 South Gull Lake  
Dr Richland, MI  
49083 USA



## LIGHT SOURCE OUTPUT(JJ):

40	14W/960lm
41	15W/1100lm
42	16W/1230lm
43	17W/1300lm
44	18W/1360lm
45	19W/1440lm
46	20W/1515lm
47	21W/1665lm
48	22W/1780lm
49	23W/1850lm

## DIMMING OPTIONS(OO):

51	Non-Dimmable
52	0-10V

## SECURITY RATING(RR):

Please Read our Crash Rating guidance

BDS-C40FB36-ST	ASTM C40 CRASH RATED FIXED BOLLARD
BDS-M30-FB-ST	ASTM M30 CRASH RATED FIXED BOLLARD
BDS-M30FB-SH	ASTM M30 CRASHED RATED SHALLOW BOLLARD
BDS-M30FB-SH	ASTM M30 CRASHED RATED SHALLOW BOLLARD
BDS-PU40FB36-ST	ASTM PU40 CRASH RATED FIXED BOLLARD
BDS-H40FB-ST	ASTM H40 CRASH RATED FIXED BOLLARD
BDS-H30FB-ST	ASTM H30 CRASH RATED FIXED BOLLARD

## GENERAL CHARACTERISTICS:

Voltage:	110-277V
Source Type:	LED
Operating Temperature:	-22°F~122°F
IP Rating:	IP 66
CRI	80


sales@gordonbullard.com  
www.bullardbollards.com  
1-877-964-4646



991 South Gull Lake  
Dr Richland, MI  
49083 USA


LENS COVER ON REQUEST (PP):

Code: RB




(NO UP-LIGHT)

Code: LG




(VERTICAL LENS)

Code: RP




(HORIZONTAL LENS)

Code: DF




(GRILLE)

Code: ZX



(GRILLE)

Code: LB



(LOUVER)