




CONSTRUCTIVE & DIMENSIONAL:

Application field:	Series of spot lights to be mounted on floor, wall, spike, tree with belt system or on a pole system.
Gaskets:	Silicone gaskets
Construction material:	Stainless steel AISI 316L
Diameter:	25mm(0.98")
Height:	34mm(1.37")
Height / Projection:	50cm(1.96")



ELECTRICAL:

GH1170.BAMT300EC 1170.BAM.T

Number of heads:	1
Description:	1 x 1 W LED 3000 K CRI>90 1 x 105 lm
Luminaire efficiency:	44.49 lm/W
Fixture consumption:	1.33 W
Operation Range:	350 mA
Number of circuits:	1
Driver positioning:	Remote
Control gear:	350 mA not included
Control gear type:	Electronic
Cable entry:	Brass cable gland M12 Ø 3.5/7 mm
Dimmer type:	Dim based on driver
Daisy chain wiring:	External to the luminaire with IP68 connector available as an accessory
Cable type:	FR5FOEM7-AD8 2x0.5mm2
Cord length:	0.5m
Emergency:	Not available
Ambient temperature operating range:	-20 °C ÷ +35 °C

OPTICAL:




Beam angle:	31°
Swivel:	+/- 90°
Light distribution:	Symmetrical medium flood (15° - 45°)
Beam directionability:	Adjustable
Diffuser material:	Tempered glass 4mm
Diffuser finish:	Transparent - extra clear
Optics:	Anti UV technopolymer lens

LIGHTING SOURCE,

Light source:	LED
Type of bulb or LED:	LED module
Light source:	1 W
Nominal LED emission:	105lm
Color temperature:	3000K
Binning:	Step MacAdam 3
LED voltage range:	3V
Current:	350mA
Color rendering index:	CRI>90
Life Time LED:	60.000h - L80 - B10
Luminaire emission:	1 x 59lm
LED / Bulb:	Included

H(m)	φ(m)	lux med. 3000 K	lux max. 3000 K
5	2.7	3	5
4	2.2	5	8
3	1.6	9	15
2	1.1	20	33
1	0.5	80	132





H(m)	φ (m)	lux med. 3000 K	lux max. 3000 K
5	2.7	3	5
4	2.2	5	8
3	1.6	9	15
2	1.1	20	33
1	0.5	80	132



FINISH OPTIONS:

Standard Finishes

- 15 Stainless steel

ACCESSORIES:



IP 68 fast connector 4P
AC204



Stake 170mm
AC203

DIMMING TYPE:

- 101. Non-dimmable
- 102. 0-10V dimmable

sales@gordonbullard.com
www.bullardbollards.com
1-877-964-4646






991 South Gull Lake
Dr Richland, MI
49083 USA



CONSTRUCTIVE & DIMENSIONAL:

Application field:	Series of spot lights to be mounted on floor, wall, spike, tree with belt system or on a pole system.
Gaskets:	Silicone gaskets
Construction material:	Stainless steel AISI 316L
Diameter:	25mm(0.98")
Height:	34mm(1.37")
Height / Projection:	50cm(1.96")



ELECTRICAL:

GH1 170.BAMT400EC 1170.BBM.T

Number of heads:	1
Description:	1 x 1 W LED 4000 K CRI>90 1 x 116 lm
Luminaire efficiency:	49.16 lm/W
Fixture consumption:	1.33 W
Operation Range:	350 mA
Number of circuits:	1
Driver positioning:	Remote
Control gear:	350 mA not included
Control gear type:	Electronic
Cable entry:	Brass cable gland M12 Ø 3.5/7 mm
Dimmer type:	Dim based on driver
Daisy chain wiring:	External to the luminaire with IP68 connector available as an accessory
Cable type:	FR5FOEM7-AD8 2x0.5mm2
Cord length:	0.5m
Emergency:	Not available
Ambient temperature operating range:	-20 °C ÷ +35 °C

OPTICAL:

Beam angle:	31°
Swivel:	+/- 90°
Light distribution:	Symmetrical medium flood (15° - 45°)
Beam directionability:	Adjustable
Diffuser material:	Tempered glass 4mm
Diffuser finish:	Transparent - extra clear
Optics:	Anti UV technopolymer lens

LIGHTING SOURCE,

Light source:	LED
Type of bulb or LED:	LED module
Light source:	1 W
Nominal LED emission:	116 lm
Color temperature:	4000K
Binning:	Step MacAdam 3
LED voltage range:	3V
Current:	350mA
Color rendering index:	CRI>90
Life Time LED:	60.000h - L80 - B10
Luminaire emission:	1 x 66lm
LED / Bulb:	Included




H(m)	φ(m)	lux med. 4000 K	lux max. 4000 K
5	2.7	4	6
4	2.2	6	9
3	1.6	10	16
2	1.1	22	36
1	0.5	88	146



sales@gordonbullard.com
www.bullardbollards.com
1-877-964-4646



991 South Gull Lake
Dr Richland, MI
49083 USA



H(m)	φ (m)	lux med. 4000 K	lux max. 4000 K
5	2.7	4	6
4	2.2	6	9
3	1.6	10	16
2	1.1	22	36
1	0.5	88	146



FINISH OPTIONS:

Standard Finishes

- 15 Stainless steel

ACCESSORIES:



IP 68 fast connector 4P
AC204



Stake 170mm
AC203

DIMMING TYPE:

- 101. Non-dimmable
- 102. 0-10V dimmable

sales@gordonbullard.com
www.bullardbollards.com
1-877-964-4646



991 South Gull Lake
Dr Richland, MI
49083 USA