






CONSTRUCTIVE & DIMENSIONAL:



H(m)	φ(m)	lux med. 3000 K	lux max. 3000 K
5	4.3	4	7
4	3.4	6	10
3	2.6	11	18
2	1.7	25	41
1	0.9	99	165



Application field: Series of spot lights to be mounted on floor, wall, spike, tree with belt system or on a pole system.

Gaskets: Silicone gaskets

Construction material: Stainless steel AISI 316L

External screws: : Stainless steel A4-70 treated with highly antioxidant water-repellent lubricating solution

Diameter: 35mm(1.37")

Height: 38mm(1.49")

Height / Projection: 58cm(2.28")

ELECTRICAL:

GH1171.BAFT300EL 1171.24BDM.T

Number of heads: 1

Description: 1 x 1.5 W LED 3000 K CRI>90 1 x 146 lm

Luminaire efficiency: 56.14 lm/W

Fixture consumption: 2 W

Operation Range: 24 V DC

Number of circuits: 1

Driver positioning: Remote

Control gear: 24 V DC not included

Control gear type: Electronic

Cable entry: Brass cable gland M12 Ø 3.5/7 mm

Dimmer type: Dim based on driver

Daisy chain wiring: External to the luminaire with IP68 connector available as an accessory

Cable type: FR5FOEM7-AD8 2x0.5mm2

Cord length: 0.5m

Emergency: Not available

Ambient temperature operating range: -20 °C ÷ +35 °C

OPTICAL:

Beam angle: 46°

Swivel: +/- 90°

Light distribution: Symmetrical wide beam (45° - 125°)

Beam directionability: Adjustable

Diffuser material: Tempered glass 4mm

Diffuser finish: Transparent - extra clear

Optics: Anti UV technopolymer lens

LIGHTING SOURCE,

Light source: LED

Type of bulb or LED: LED module

Light source: 1.5 W

Nominal LED emission: 146lm

Color temperature: 3000K

Binning: Step MacAdam 3

LED voltage range: 3V

Current: 500 mA

Color rendering index: CRI>90

Life Time LED: 60.000h - L80 - B10




Luminaire emission: 1 x 112 lm

LED / Bulb: Included

sales@gordonbullard.com
www.bullardbollards.com
1-877-964-4646



991 South Gull Lake
Dr Richland, MI
49083 USA



H(m)	φ(m)	lux med. 3000 K	lux max. 3000 K
5	4.3	4	7
4	3.4	6	10
3	2.6	11	18
2	1.7	25	41
1	0.9	99	165



FINISH OPTIONS:

Standard Finishes

- 15 Stainless steel

ACCESSORIES:



IP 68 fast connector 4P
AC204



Stake 170mm
AC203




DIMMING TYPE:

- 101. Non-dimmable
- 102. 0-10V dimmable

sales@gordonbullard.com
www.bullardbollards.com
1-877-964-4646



991 South Gull Lake
Dr Richland, MI
49083 USA



H(m)	φ(m)	lux med. 4000 K	lux max. 4000 K
5	4.3	4	7
4	3.4	7	11
3	2.6	12	20
2	1.7	27	46
1	0.9	110	183



CONSTRUCTIVE & DIMENSIONAL:

Application field:	Series of spot lights to be mounted on floor, wall, spike, tree with belt system or on a pole system.
Gaskets:	Silicone gaskets
Construction material:	Stainless steel AISI 316L
External screws:	Stainless steel A4-70 treated with highly antioxidant water-repellent lubricating solution
Diameter:	35mm(1.37")
Height:	38mm(1.49")
Height / Projection:	58cm(2.28")

ELECTRICAL:

GH1171.BAFT400EL 1171.24BEM




Number of heads:	1
Description:	1 x 1.5 W LED 4000 K CRI>90 1 x 162 lm
Luminaire efficiency:	62.3 lm/W
Fixture consumption:	2 W
Operation Range:	24 V DC
Number of circuits:	1
Driver positioning:	Remote
Control gear:	24 V DC not included
Control gear type:	Electronic
Cable entry:	Brass cable gland M12 Ø 3.5/7 mm
Dimmer type:	Dim based on driver
Daisy chain wiring:	External to the luminaire with IP68 connector available as an accessory
Cable type:	FR5FOEM7-AD8 2x0.5mm2
Cord length:	0.5m
Emergency:	Not available
Ambient temperature operating range:	-20 °C ÷ +35 °C

OPTICAL:

Beam angle:	46°
Swivel:	+/- 90°
Light distribution:	Symmetrical wide beam (45° - 125°)
Beam directionability:	Adjustable
Diffuser material:	Tempered glass 4mm
Diffuser finish:	Transparent - extra clear
Optics:	Anti UV technopolymer lens

LIGHTING SOURCE,

Light source:	LED
Type of bulb or LED:	LED module
Light source:	1.5 W
Nominal LED emission:	162 lm
Color temperature:	4000K
Binning:	Step MacAdam 3
LED voltage range:	3V
Current:	500mA
Color rendering index:	CRI>90
Life Time LED:	60.000h - L80 - B10
Luminaire emission:	1 x 125lm
LED / Bulb:	Included



H(m)	φ(m)	lux med. 4000 K	lux max. 4000 K
5	4.3	4	7
4	3.4	7	11
3	2.6	12	20
2	1.7	27	46
1	0.9	110	183



FINISH OPTIONS:

Standard Finishes

- 15 Stainless steel

ACCESSORIES:



IP 68 fast connector 4P
AC204



Stake 170mm
AC203

DIMMING TYPE:

- 101. Non-dimmable
- 102. 0-10V dimmable

sales@gordonbullard.com
www.bullardbollards.com
1-877-964-4646



991 South Gull Lake
Dr Richland, MI
49083 USA