Product code: SLK PRO 30



SOLAR FLOOD LIGHT



Introducing the SLKPRO, SOLUX's innovative solar flood light solution designed for exceptional performance and reliability. Unlike most common solution offering low quality lithium ION, the SLKPRO features a durable LifePO4 battery, ensuring consistent illumination and reducing the frequency of battery replacements, making it an eco-friendly choice.

With the **included remote control**, users can conveniently adjust settings such as brightness levels, lighting modes, and timers. The SLKPRO also incorporates a **microwave movement sensor**, enhancing security and conserving energy by activating the light only when motion is detected.

Designed for **easy installation**, the SLKPRO is crafted from **high-quality die-casting aluminum**, providing durability and effective heat dissipation. This versatile solar flood light is ideal for various residential, commercial, and industrial settings, offering a dependable and efficient outdoor lighting solution that stands out from the competition.

SLKPRO - SOLAR FLOOD LIGHT / Page 1 of 4

sales@gordonbullard.com www.bullardbollards.com 1-877-964-4646




991 South Gull Lake Dr Richland, MI 49083 ISA

MAIN FEATURES

MOTION SENSOR

The microwave motion sensor integrated into the SLKPRO offers enhanced security and energy efficiency. This advanced technology detects movement within its range, activating the light only when necessary, ensuring optimal performance and energy conservation.



LIFEPO4 BATTERY

The SLKPRO incorporates the latest technology in solar lighting solutions, providing a reliable and long-lasting performance that spans over a decade. While the initial investment may be higher, the **exceptional durability** and **extended lifespan of over 10 years** make it a worthwhile choice for your lighting needs.



EXTREME TEMPERATURE

14°F to 158°F (- 40 °F OPTIONAL) - 10 °C TO 70 °C (- 40 °C OPTIONAL)

When Standard Lithium LiFePo4 batteries enjoy a working temperature range from 14°F to 158°F (-10°C TO 70 °C). Solux offers as optional a new Special LIFEPO4 battery with working range of -40°F to 158°F (-40 °C to 70 °C.)

LUMINAIRE BRACKET CAP


The SLKPRO features a bracket cap on the flood light, allowing for easy installation and convenient **angle adjustment**, ensuring optimal illumination and **user-friendly setup**.

REMOTE CONTROL

The SLKPRO is equipped with a remote control that enables you to effortlessly adjust various working modes according to the season, activate the movement sensor, and modify timer settings, providing a tailored lighting experience to suit your needs.

SOLAR PANEL

The SLKPRO includes a **high-quality Grade A monocrystalline solar panel**, accompanied by an integrated fixation system, ensuring efficient **energy conversion** and **hassle-free installation**.



SLKPRO - SOLAR FLOOD LIGHT / Page 2 of 4

sales@gordonbullard.com www.bullardbollards.com 1-877-964-4646



Due to the dynamic nature of lighting products and the associated technologies, luminaire data on all sheet sheets is subject to change at the discretion of Gordon Bullard LLC and associated companies.

© Bullard & Company 2023 All Rights Reserved Updated 10/21/23

SLKPRO 30

NOMINAL FLUX 5 880 LUMENS
NOMINAL POWER 30 WATTS

LIGHTING

 Efficiency
 196 Lumens/Watts

 Chips LED
 PHILIPS Luxeon 30-30 / 3000K to 6000K

 LED lifetime
 Over 50000 hours LM80

 CCT
 3000K to 6000K

BATTERY

ENERGY

ELECTRONIC

MECHANICAL


Wall /Pole Mounting Ø 225mm x 60mm x 30mm (8,86" x 2,36" x 1,18")

DIMENSIONS

How to order?

Product code - CCT - Finish Option For Example: SLKPRO30-3000K-Black





sales@gordonbullard.com www.bullardbollards.com 1-877-964-4646



SLKPRO - SOLAR FLOOD LIGHT / Page 4 of 4

2,36" (60mm)

© Bullard & Company 2023 All Rights Reserved Updated 10/21/23